

STP330 - 24/Vfj
STP325 - 24/Vfj
STP320 - 24/Vfj

330 Watt

DOUBLE GLASS SOLAR MODULE



Features



High module conversion efficiency

Module efficiency up to 16.8% achieved through advanced cell technology and manufacturing capabilities



Withstanding harsh environment

Reliable quality leads to a better sustainability even in harsh environment like desert, farm and coastline



Positive tolerance

Guaranteed positive tolerance of 5 W delivers higher output



Suntech current sorting process

System output maximized by reducing mismatch losses up to 2% with modules sorted & packaged by amperage



Extended wind and snow load tests

Module certified to withstand extreme wind (2400 Pascal) and snow loads (2400 Pascal) *



High system voltage Compatible


Maximum 1500 V DC system voltage reduces total system cost

Certifications and standards:
IEC 61215, IEC 61730, conformity to CE



Trust Suntech to Deliver Reliable Performance Over Time


- World-class manufacturer of crystalline silicon photovoltaic modules
- Unrivaled manufacturing capacity and world-class technology
- Rigorous quality control meeting the highest international standards: ISO 9001: 2008, ISO 14001: 2004 and ISO17025: 2005
- Regular independently checked production process from international accredited institute/company
- Tested for harsh environments (ammonia corrosion and sand blowing testing: IEC 62716, DIN EN 60068-2-68)**
- Long-term reliability tests
- 2 x 100% EL inspection ensuring defect-free modules



Frameless design

- Glass-Glass structure
- Economize grounding hardware
- Heat strengthened glass ensures high mechanical capability

Industry-leading Warranty based on nominal power



- 97.5% in the first year, thereafter, for years two (2) through thirty (30), 0.5% maximum decrease from MODULE's nominal power output per year, ending with the 83% in the 30th year after the defined WARRANTY STARTING DATE.***
- 12-year product warranty
- 30-year linear performance warranty



IP67 Rated Junction Box

IP67 rated junction box supports installations in multiple orientations. High reliable performance, low resistance connectors ensure maximum output for the highest energy production


* Please refer to Suntech Double Glass Module Installation Manual for details.

** Please refer to Suntech Product Near-coast Installation Manual for details.

*** Please refer to Suntech Product Warranty for details.

Made in China

STP330 - 24/Vfj
STP325 - 24/Vfj
STP320 - 24/Vfj




Electrical Characteristics

| STC | STP330-24/Vfj | STP325-24/Vfj | STP320-24/Vfj |
|---------------------------------|------------------|---------------|---------------|
| Maximum Power at STC (Pmax) | 330 W | 325 W | 320 W |
| Optimum Operating Voltage (Vmp) | 38.4 V | 38.2 V | 38.0 V |
| Optimum Operating Current (Imp) | 8.60 A | 8.51 A | 8.43 A |
| Open Circuit Voltage (Voc) | 46.4 V | 46.1 V | 45.9 V |
| Short Circuit Current (Isc) | 9.14 A | 9.06 A | 8.98 A |
| Module Efficiency | 16.8% | 16.6% | 16.3% |
| Operating Module Temperature | -40 °C to +85 °C | | |
| Maximum System Voltage | 1500 V DC (IEC) | | |
| Maximum Series Fuse Rating | 15 A | | |
| Power Tolerance | 0/+5 W | | |

STC: Irradiance 1000 W/m², module temperature 25 °C, AM=1.5; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3%

| NOCT | STP330-24/Vfj | STP325-24/Vfj | STP320-24/Vfj |
|---------------------------------|---------------|---------------|---------------|
| Maximum Power at NOCT (Pmax) | 239.2 W | 235.3 W | 232.0 W |
| Optimum Operating Voltage (Vmp) | 34.4 V | 34.2 V | 34.1 V |
| Optimum Operating Current (Imp) | 6.94 A | 6.87 A | 6.81 A |
| Open Circuit Voltage (Voc) | 42.1 V | 41.8 V | 41.6 V |
| Short Circuit Current (Isc) | 7.39 A | 7.33 A | 7.26 A |

NOCT: Irradiance 800 W/m², ambient temperature 20 °C, AM=1.5, wind speed 1 m/s; Best in Class AAA solar simulator (IEC 60904-9) used, power measurement uncertainty is within +/- 3%




Temperature Characteristics

| | |
|---|------------|
| Nominal Operating Cell Temperature (NOCT) | 46±2°C |
| Temperature Coefficient of Pmax | -0.39 %/°C |
| Temperature Coefficient of Voc | -0.32 %/°C |
| Temperature Coefficient of Isc | 0.049 %/°C |

Mechanical Characteristics

| | |
|------------------|--|
| Solar Cell | Polycrystalline silicon 6 inches |
| No. of Cells | 72 (6 × 12) |
| Dimensions | 1980 × 990 × 5mm without J-box |
| Weight | 23.3 kgs |
| Front/Back Glass | 2.0 mm tempered glass |
| Junction Box | IP67 rated (3 bypass diodes) |
| Output Cables | 4.0 mm ² (0.006 inches ²), symmetrical lengths (-) 1000mm (39.4 inches) and (+) 1000 mm (39.4 inches) |
| Connectors | Genuine MC4 |

Dealer information



Packing Configuration

| Container | 20' GP | 40' GP | 40' HC |
|-----------------------|--------|--------|--------|
| Pieces per pallet | 38 | 38 | 38 |
| Pallets per container | 5 | 11 | 22 |
| Pieces per container | 190 | 418 | 836 |

Product specification is subjected to change for improvement. Information on how to install and operate this product is available in the installation instruction. All values indicated in this data sheet are subject to change without prior announcement. The specifications may vary slightly. All specifications are in accordance with standard EN 50380. Color differences of the modules relative to the figures as well as discolorations of/in the modules which do not impair their proper functioning are possible and do not constitute a deviation from the specification.